

ARMAFLEX Isolationsschlauch XG, 9mm

Schwarz, Anwendungsbereich -50°C bis 105°C,
Brandverhalten: schwerentflammbar, Brandkennziffer 5 (200°C)

SAP-Nr.	Artikel-Nr.	Stärke	Ø D	VE	CHF
SPAETER	Lieferanten	mm	mm	m	m
209646	XG-09x006	9	6	352	3.47
209647	XG-09x008	9	8	300	3.57
209648	XG-09x010	9	10	266	3.73
209649	XG-09x012	9	12	234	3.93
209650	XG-09x015	9	15	192	4.09
209651	XG-09x018	9	18	166	4.35
209652	XG-09x020	9	20	140	4.66
209653	XG-09x022	9	22	136	4.97
209654	XG-09x025	9	25	108	5.18
209655	XG-09x028	9	28	98	5.33
209656	XG-09x032	9	32	80	5.74
209657	XG-09x035	9	35	76	6.11
209658	XG-09x040	9	40	66	6.78
209659	XG-09x042	9	42	60	6.99
209660	XG-09x048	9	48	50	8.23
209661	XG-09x054	9	54	46	9.47
209662	XG-09x060	9	60	36	11.85
209663	XG-09x064	9	64	34	13.14
209664	XG-09x070	9	70	32	3.93
209665	XG-09x076	9	76	26	15.78
209666	XG-09x089	9	89	20	19.20
209667	XG-09x102	9	102	20	3.93
209668	XG-09x108	9	108	20	3.93
209669	XG-09x114	9	114	20	31.05
209670	XG-09x125	9	125	20	3.93
209671	XG-09x140	9	140	20	3.93
209672	XG-09x160	9	160	16	3.93



ARMAFLEX Isolationsschlauch XG, 13mm

Schwarz, Anwendungsbereich -50°C bis 105°C,
Brandverhalten: schwerentflammbar, Brandkennziffer 5(200°C)

SAP-Nr.	Artikel-Nr.	Stärke	Ø D	VE	CHF
SPAETER	Lieferanten	mm	mm	m	m
209673	XG-13X006	13	6	222	4.55
209674	XG-13X008	13	8	210	4.86
209675	XG-13x010	13	10	172	5.18
209676	XG-13X012	13	12	162	5.43
209677	XG-13X015	13	15	136	6.16
209678	XG-13X018	13	18	118	6.73
209679	XG-13X020	13	20	114	6.99
209680	XG-13X022	13	22	108	7.25
209681	XG-13X025	13	25	100	7.50
209682	XG-13X028	13	28	78	7.97
209683	XG-13X032	13	32	20	8.80
209684	XG-13X035	13	35	58	9.57
209685	XG-13X040	13	40	18	10.45
209686	XG-13X042	13	42	48	10.82
209687	XG-13X048	13	48	40	12.94
209688	XG-13X050	13	50	36	13.82

