

### ARMAFLEX Isolationsschlauch XG, 25mm

Schwarz, Anwendungsbereich -50°C bis 105°C,  
Brandverhalten: schwerentflammbar, Brandkennziffer 5(200°C).2

SAP-Nr.	Artikel-Nr.	Stärke	Ø D	VE	CHF
SPAETER	Lieferanten	mm	mm	m	m
217691	XG-25x015	25	15	48	16.66
217692	XG-25x018	25	18	42	17.13
217693	XG-25x020	25	20	38	17.10
217694	XG-25x022	25	22	36	18.22
217695	XG-25x028	25	28	32	21.42
217696	XG-25x032	25	32	28	21.90
217697	XG-25x035	25	35	24	23.60
217698	XG-25x040	25	40	24	27.25
217699	XG-25x042	25	42	24	30.02
217700	XG-25x048	25	48	20	34.47
217701	XG-25x054	25	54	18	38.97
217702	XG-25x060	25	60	18	42.28
217703	XG-25x064	25	64	16	44.25
217704	XG-25x076	25	76	16	50.09
217705	XG-25x089	25	89	12	55.63
217706	XG-25x102	25	102	6	69.60
217707	XG-25x108	25	108	6	76.02
217708	XG-25x114	25	114	6	80.89
217709	XG-25x133	25	133	4	98.22
217710	XG-25x140	25	140	4	104.59
217711	XG-25x160	25	160	4	112.50
217712	XG-25x168	25	168	4	115.10



### ARMAFLEX Isolationsschlauch XG, 32mm

Schwarz, Anwendungsbereich -50°C bis 105°C,  
Brandverhalten: schwerentflammbar, Brandkennziffer 5(200°C).2

SAP-Nr.	Artikel-Nr.	Stärke	Ø D	VE	CHF
SPAETER	Lieferanten	mm	mm	m	m
217713	XG-32x018	32	18	32	24.48
217714	XG-32x022	32	22	24	26.03
217715	XG-32x028	32	28	24	28.82
217716	XG-32x035	32	35	18	33.43
217717	XG-32x040	32	40	16	39.33
217718	XG-32x042	32	42	16	41.71
217719	XG-32x048	32	48	12	45.23
217720	XG-32x054	32	54	12	52.22
217721	XG-32x060	32	60	10	56.30
217722	XG-32x064	32	64	10	59.10
217723	XG-32x070	32	70	10	63.81
217724	XG-32x076	32	76	10	67.12
217725	XG-32x089	32	89	10	74.42
217726	XG-32x102	32	102	6	84.46
217727	XG-32x108	32	108	6	99.57
217728	XG-32x114	32	114	4	108.62
217729	XG-32x125	32	125	4	119.75
217730	XG-32x133	32	133	4	127.82
217731	XG-32x140	32	140	4	134.81
217732	XG-32x160	32	160	2	157.22
217733	XG-32x168	32	168	2	176.90

