

### ARMAFLEX Isolationsschlauch XG, 40mm

Schwarz, Anwendungsbereich -50°C bis 105°C,  
Brandverhalten: schwerentflammbar, Brandkennziffer 5(200°C).2

SAP-Nr.	Artikel-Nr.	Stärke	Ø D	VE	CHF
SPAETER	Lieferanten	mm	mm	m	m
217734	XG-40X28	40	28	24	36.02
217735	XG-40X35	40	35	22	41.81
217736	XG-40X42	40	42	16	52.16
217737	XG-40x048	40	48	12	56.56
217738	XG-40X054	40	54	12	65.26
217739	XG-40x060	40	60	10	70.59
217740	XG-40X064	40	64	10	72.76
217741	XG-40x076	40	76	8	79.18
217742	XG-40X089	40	89	6	87.15
217743	XG-40x102	40	102	4	105.57
217744	XG-40X108	40	108	4	108.68
217745	XG-40x114	40	114	4	119.34
217746	XG-40X140	40	140	2	145.78
217747	XG-40x160	40	160	2	170.15
217748	XG-40X168	40	168	2	192.25



### ARMAFLEX Isolationsschlauch XG, 19mm, selbstklebend

Schwarz, Anwendungsbereich -50°C bis 105°C,  
Brandverhalten: schwerentflammbar, Brandkennziffer 5(200°C).2

SAP-Nr.	Artikel-Nr.	Stärke	Ø D	VE	CHF
SPAETER	Lieferanten	mm	mm	m	m
217769	XG-19X018-A	19	18	60	13.40
217770	XG-19X022-A	19	22	56	14.90
217771	XG-19X028-A	19	28	48	17.60
217772	XG-19X035-A	19	35	36	19.98
217773	XG-19X042-A	19	42	32	22.36
217774	XG-19X048-A	19	48	24	26.75
217775	XG-19X054-A	19	54	24	30.02
217776	XG-19X060-A	19	60	24	33.48
217777	XG-19X076-A	19	76.1	16	39.80
217778	XG-19X089-A	19	88.9	16	44.61

