

Flanschdichtung, asbestfrei, ND 6

Dicke 2 mm, für glatte Flanschen (VSM 18695 oder DIN 2573), Vorschweisflanschen (VSM 18716 oder DIN 2631), Blindflanschen (VSM 18703 oder DIN 2527)

SAP-Nr.	NW	d	D	CHF
SPAETER		mm	mm	Stk.
124981	125	141	182	6.30
213155	150	160	207	7.40
124982	150	169	207	7.75
213156	175	195	237	5.50
144933	200	220	262	12.50
144934	250	274	318	9.15
124985	300	325	373	14.10
213157	350	369	423	22.40
213158	400	420	473	27.10



Flanschdichtung, asbestfrei, ND 10 / ND 16 / ND 40

Dicke 2 mm, für glatte Flanschen (VSM 18696 oder DIN 2576), Vorschweisflanschen (VSM 18717 oder DIN 2632), Blindflanschen (VSM 18703 oder DIN 2527)

SAP-Nr.	Druckstufe	NW	d	D	CHF
SPAETER			mm	mm	Stk.
176217	10 / 16	10	18	45	0.75
176218	10 / 16	15	22	50	0.85
124986	10 / 40	20	28	60	0.95
124987	10 / 40	25	35	70	1.50
124988	10 / 40	32	43	82	1.95
124989	10 / 40	40	49	92	2.45
124990	10 / 40	50	61	107	3.30
124991	10 / 40	65	77	127	4.45
124992	10 / 40	80	90	142	5.50
124993	10 / 16	100	115	162	6.20
124994	10 / 16	125	141	192	8.20
144935	10 / 16	150	169	218	11.15
144936	10 / 16	200	220	273	15.75
176219	10 / 16	250	274	328	7.70
176220	10 / 16	300	325	378	9.60
208108	10	350	369	438	16.20
208109	10	400	420	490	18.05
144937	10 / 40	10	18	45	0.40



Flanschdichtung, asbestfrei, ND 40

Dicke 2 mm, für glatte Flanschen (VSM 18699), Vorschweisflanschen (VSM 18720 oder DIN 2635), Blindflanschen (VSM 18703 oder DIN 2527)

SAP-Nr.	NW	d	D	CHF
SPAETER		mm	mm	Stk.
213160	100	115	168	6.85
213161	125	141	195	8.40
213162	150	169	225	11.75
213163	200	220	292	17.85

