


Flachsenker HSS, Kernloch

Fraise à lamer HSS, avant-trou

881.102



BECK

- BECK 111100
- DIN 373

- für Kernloch

- BECK 111100
- DIN 373

- Pour avant-trou

Art. Nr. N° d'art.	für Gewinde Pour filetage	d1 mm	d3 mm	l1 mm	d2 mm	WI CHF/Stk CHF/pce
881.102.100	M3	6	2.5	71	5	16.10
881.102.200	M4	8	3.3	71	5	14.90
881.102.300	M5	10	4.2	80	8	14.10
881.102.400	M6	11	5	80	8	15.10
881.102.500	M8	15	6.8	100	12.5	23.40
881.102.600	M10	18	8.5	100	12.5	29.10
881.102.700	M12	20	10.2	100	12.5	32.40



Flachsenker HSS, fein

Fraise à lamer HSS, fine

881.114



BECK

- BECK 112300

- für Durchgangsloch, fein  
- mit Morsekegelschaft

- BECK 112300

- Pour trou débouchant, fin  
- Avec queue cône morse

Verwendung

Zum Versenken von Innensechskantschrauben DIN 912, 6912, 7984 und Zylinderschrauben mit Schlitz DIN 84. Für Senkungen nach DIN 74, Blatt 2, Form H, J, K.

Application

Pour noyer les vis à six pans creux DIN 912, 6912, 7984 et vis à tête cylindrique à fente DIN 84. Pour logements DIN 74, feuille 2, forme H, J, K

Art. Nr. N° d'art.	für Schrauben Pour vis	d1 mm	d3 mm	l1 mm	MK CM	WI CHF/Stk CHF/pce
881.114.100	M10	18	10.5	150	2	43.70
881.114.200	M12	20	13	150	2	47.00
881.114.300	M14	24	15	160	2	54.10
881.114.400	M16	26	17	190	3	61.20
881.114.500	M18	30	19	190	3	72.70
881.114.600	M20	33	21	190	3	84.30
881.114.800	M24	40	25	205	3	118.70

