



- DC
- DIN 13

- kurzer Schaft
- gerade Nuten
- \varnothing 3.15 mm (\varnothing Schaft) aus PM

Verwendung

Für den Hand- und Maschinengebrauch.

- DC
- DIN 13

- Queue courte
- Goujures droites
- \varnothing 3.15 mm (\varnothing queue) en métal fritté

Application

Pour utilisation manuelle ou en machine.



| Art. Nr. N° d'art. | Typ Type | \varnothing | Steigung mm Pas mm | \varnothing Schaft mm \varnothing queue mm | L mm | l Gewinde mm Long. filetée mm | Vierkant mm Carré mm | WB CHF/Stk CHF/pce |
|-----------------------|-------------|---------------|-----------------------|---|------|----------------------------------|-------------------------|--------------------------|
| 844.120.220 | N 1110-2 | M 2 | 0.4 | 2.5 | 41 | 8 | 2.10 | 20.00 |
| 844.120.280 | N 1110-2 | M 2.5 | 0.45 | 2.8 | 44.5 | 9.5 | 2.24 | 16.50 |
| 844.120.300 | N 1110-2 | M 2.6 | 0.45 | 2.8 | 44.5 | 9.5 | 2.24 | 18.00 |
| 844.120.320 | N 1110-2 | M 3 | 0.5 | 3.15 | 48 | 11 | 2.50 | 13.50 |
| 844.120.340 | N 1110-2 | M 3.5 | 0.6 | 3.55 | 50 | 13 | 2.80 | 16.30 |
| 844.120.360 | N 1110-2 | M 4 | 0.7 | 4 | 53 | 13 | 3.15 | 13.50 |
| 844.120.400 | N 1110-2 | M 5 | 0.8 | 5 | 58 | 16 | 4.00 | 14.70 |
| 844.120.420 | N 1110-2 | M 6 | 1 | 6.3 | 66 | 19 | 5.00 | 14.70 |
| 844.120.460 | N 1110-2 | M 8 | 1.25 | 8 | 72 | 22 | 6.30 | 16.50 |
| 844.120.500 | N 1110-2 | M 10 | 1.5 | 10 | 80 | 24 | 8.00 | 20.50 |
| 844.120.540 | N 1210-2 | M 12 | 1.75 | 9 | 89 | 29 | 7.10 | 26.50 |
| 844.120.560 | N 1210-2 | M 14 | 2 | 11.2 | 95 | 30 | 9.00 | 36.00 |
| 844.120.580 | N 1210-2 | M 16 | 2 | 12.5 | 102 | 32 | 10.00 | 42.00 |
| 844.120.600 | N 1210-2 | M 18 | 2.5 | 14 | 112 | 37 | 11.20 | 58.00 |
| 844.120.620 | N 1210-2 | M 20 | 2.5 | 14 | 112 | 37 | 11.20 | 66.00 |
| 844.120.640 | N 1210-2 | M 22 | 2.5 | 16 | 118 | 38 | 12.50 | 79.00 |
| 844.120.660 | N 1210-2 | M 24 | 3 | 18 | 130 | 45 | 14.00 | 90.00 |
| 844.120.680 | N 1210-2 | M 27 | 3 | 20 | 135 | 45 | 16.00 | 125.00 |
| 844.120.700 | N 1210-2 | M 30 | 3.5 | 20 | 138 | 48 | 16.00 | 156.00 |

Einsatz für DC-Anwendungsbereich "N", normale Werkstoffe.

Domaine d'application "N" de DC, matériaux normaux.