



PRECITOOL

- PRECITOOL 135110
- DIN 13 / 376

- PRECITOOL 135110
- DIN 13 / 376

Art. Nr. N° d'art.	d1 mm	P mm	l1 mm	l2 mm	d2 mm	a mm	l3 mm	Kernloch Ø mm Avant-trou Ø mm	WM CHF/Stk CHF/pce
881.561.100	M5	0.8	70	16	3.5	2.7	6	4.2	14.00
881.561.150	M6	1	80	19	4.5	3.4	6	5	14.00
881.561.200	M8	1.25	90	22	6.0	4.9	8	6.8	16.50
881.561.250	M10	1.5	100	24	7.0	5.5	8	8.5	23.80
881.561.300	M12	1.75	110	29	9.0	7	10	10.2	26.00
881.561.350	M14	2	110	30	11.0	9	12	12	39.50
881.561.400	M16	2	110	32	12.0	9	12	14	41.00



- DC
- DIN 371 / 376 / 13

- Einzelschneider
- mit Schälanschnitt
- N 330-4 nach DIN 371
- N 430-4 nach DIN 376

Verwendung

Für Durchgangslöcher, für Messing langspanend.

- DC
- DIN 371 / 376 / 13

- 1 passe
- Avec entrée à hélice
- N 330-4 selon DIN 371
- N 430-4 selon DIN 376

Application

Pour trous débouchants dans le laiton à copeaux longs.



Art. Nr. N° d'art.	Typ Type	Ø	Steigung mm Pas mm	Ø Schaft mm Ø queue mm	L mm	l Gewinde mm Long. filetée mm	Vierkant mm Carré mm	WB CHF/Stk CHF/pce
844.277.140	N 330-4	M 3	0.5	3.5	56	12	2.7	14.80
844.277.160	N 330-4	M 3.5	0.6	4	56	13	3.0	17.70
844.277.180	N 330-4	M 4	0.7	4.5	63	14	3.4	14.90
844.277.200	N 330-4	M 5	0.8	6	70	15	4.90	15.50
844.277.220	N 330-4	M 6	1	6	80	17	4.90	15.50
844.277.240	N 430-4	M 8	1.25	8	90	20	6.2	17.60
844.277.260	N 430-4	M 10	1.5	10	100	22	8.0	22.40
844.277.280	N 430-4	M 12	1.75	9	110	24	7.0	27.70

Anwendungsbereich "N", Gruppe 63 / 71 / 72

Domaine d'application "N" de DC, groupe 63 / 71 / 72