



- JOBBOSS 140020
- DIN 22568

- mit beidseitigem Schälanschnitt, ab M3
- Form B geschlossen
- bis M1,4 Toleranz 6h

- JOBBOSS 140020
- DIN 22568

- Avec entrée hélicoïdale des deux côtés, à partir de M3
- Forme B fermée
- Jusqu'à M1,4 tolérance 6h

Art. Nr. N° d'art.	d1 mm	P mm	D mm	H mm	CHF/Stk CHF/pce
881.885.200	M2	0.4	16	5	16.90
881.885.240	M2.5	0.45	16	5	15.70
881.885.280	M3	0.5	20	5	14.40
881.885.320	M4	0.7	20	5	14.40
881.885.340	M5	0.8	20	7	14.40
881.885.360	M6	1	20	7	14.40
881.885.400	M8	1.25	25	9	15.60
881.885.500	M10	1.5	30	11	19.40
881.885.540	M12	1.75	38	14	25.20
881.885.560	M14	2	38	14	25.90
881.885.580	M16	2	45	18	33.80
881.885.600	M18	2.5	45	18	35.50
881.885.620	M20	2.5	45	18	35.50
881.885.640	M22	2.5	55	22	52.10
881.885.660	M24	3	55	22	52.10
881.885.680	M27	3	65	25	81.50
881.885.700	M30	3.5	65	25	81.50



- JOBBOSS 140320
- DIN 24231

- mit beidseitigem Schälanschnitt, ab M3
- Form B geschlossen

- JOBBOSS 140320
- DIN 24231

- Avec entrée à hélice des 2 côtés, dès M3
- Forme B fermée

Art. Nr. N° d'art.	Typ Type	d1 mm	Gänge/Zoll Filets/pouce	D mm	H mm	CHF/Stk CHF/pce
881.903.100	G1/8	9.73	28	30	11	31.80
881.903.200	G1/4	13.16	19	38	10	33.50
881.903.300	G3/8	16.66	19	45	14	45.00
881.903.400	G1/2	20.96	14	45	14	45.00
881.903.500	G5/8	22.91	14	55	16	71.40
881.903.600	G3/4	26.44	14	55	16	72.50
881.903.700	G7/8	30.20	14	65	18	103.60
881.903.800	G1	33.25	11	65	18	99.20

