

Bohrnutenfräser HSS-AL

Fraise à rainurer HSS-AL

882.186



PRECITOOL

- PRECITOOL 162550
- DIN 844

- Schneidentoleranz e8
- Schafttoleranz h6
- scharfkantig

- PRECITOOL 162550
- DIN 844

- Tolérance des arêtes de coupe e8
- Tolérance de queue h6
- Angles vifs

| Art. Nr.<br>N° d'art. | d1 mm | l1 mm | l2 mm | d2 mm | WM<br>CHF/Stk<br>CHF/pce |
|-----------------------|-------|-------|-------|-------|--------------------------|
| 882.186.100           | 3.0   | 52    | 8     | 6.0   | 18.60                    |
| 882.186.130           | 4.0   | 55    | 11    | 6.0   | 18.60                    |
| 882.186.190           | 5.0   | 57    | 13    | 6.0   | 18.60                    |
| 882.186.250           | 6.0   | 57    | 13    | 6.0   | 18.70                    |
| 882.186.310           | 8.0   | 69    | 19    | 8.0   | 21.20                    |
| 882.186.370           | 10.0  | 72    | 22    | 10.0  | 23.20                    |
| 882.186.430           | 12.0  | 83    | 26    | 12.0  | 27.90                    |
| 882.186.490           | 14.0  | 83    | 26    | 12.0  | 36.00                    |
| 882.186.550           | 16.0  | 92    | 32    | 16.0  | 38.30                    |
| 882.186.580           | 18.0  | 92    | 32    | 16.0  | 49.00                    |
| 882.186.610           | 20.0  | 104   | 38    | 20.0  | 50.60                    |



Bohrnutenfräser HSS-AL

Fraise à rainurer HSS-AL

882.195



PRECITOOL

- PRECITOOL 162650
- DIN 844

- Schneidentoleranz e8
- Schafttoleranz h6
- scharfkantig

- PRECITOOL 162650
- DIN 844

- Tolérance des arêtes de coupe e8
- Tolérance de queue h6
- Angles vifs

| Art. Nr.<br>N° d'art. | d1 mm | l1 mm | l2 mm | d2 mm | WM<br>CHF/Stk<br>CHF/pce |
|-----------------------|-------|-------|-------|-------|--------------------------|
| 882.195.100           | 2.0   | 54    | 10    | 6.0   | 15.50                    |
| 882.195.150           | 3.0   | 56    | 12    | 6.0   | 15.50                    |
| 882.195.200           | 4.0   | 63    | 19    | 6.0   | 15.50                    |
| 882.195.250           | 5.0   | 68    | 24    | 6.0   | 15.50                    |
| 882.195.300           | 6.0   | 68    | 24    | 6.0   | 15.50                    |
| 882.195.350           | 8.0   | 82    | 38    | 8.0   | 19.20                    |
| 882.195.400           | 10.0  | 95    | 45    | 10.0  | 23.00                    |
| 882.195.450           | 12.0  | 110   | 53    | 12.0  | 24.00                    |
| 882.195.500           | 14.0  | 110   | 53    | 12.0  | 32.80                    |
| 882.195.550           | 16.0  | 123   | 63    | 16.0  | 35.60                    |
| 882.195.600           | 18.0  | 123   | 63    | 16.0  | 42.70                    |
| 882.195.650           | 20.0  | 141   | 75    | 20.0  | 52.50                    |

